



*Well-Balanced Color and Brightness,
Seamlessly Integrated into
Environment and Infrastructure*

7,000lm	WUXGA	3,000,000:1
----------------	--------------	--------------------

Item	Description	
패널	16.3mm (0.64") (16:10 비율) LCD x 3	
해상도	WUXGA (1,920 x 1,200), 6,912,000 pixels	
광원	Laser diodes (광원수명 - Nomal : 20,000h / Eco : 24,000h)	
밝기	7,000 Lumens	
명암비	3,000,000:1 (Dynamic Mode/Dynamic Contrast 1/2)	
주변조도비	85%	
스크린사이즈	0.76-7.62 m [30-300 in], 16:10 aspect ratio	
렌즈	1.6x Manual zoom (throw ratio 1.09-1.77 :1), F = 1.6-2.12, f = 15.3-24.64 mm	
단자	HDMI 1 IN / 2 IN	HDMI-19 pin x 2, Deep Color, compatible with HDCP 1.4, 4K/30p signal input, CEC supported
	COMPUTER 1 IN / 2 IN	D-sub 15pin (female) x 2 [RGB]0.7 V [p-p], 75 ohms (1.0 V [p-p], 75 ohms for sync on G) HD/SYNC, VD: TTL, high impedance, positive/negative automatic [YPP]Y: 1.0 V [p-p], including sync signal, PB/PR (CB/CR): 0.7 V [p-p], 75 ohms
	AUDIO 1 IN / 2 IN	M3 stereo mini-jack x 2 0.5 V [rms], input Impedance 22 k Ohms and more
	VARIABLE AUDIO OUT	M3 stereo mini-jack x 1 0 V [rms] to 2.0 V [rms] variable, output Impedance 2.2 k ohms and less
	SERIAL IN	D-sub 9-pin (female) x 1 for computer control (RS-232C compliant)
	LAN	RJ-45 x 1 for network control, 10Base-T, 100Base-TX, compatible with PLinkTM (Class 2)
	DIGITAL LINK/LAN	RJ-45 x 1 for network and DIGITAL LINK connection, HDBase-TTM compliant, 100Base-TX, compatible with PLinkTM (Class 2), HDCP 1.4, Deep Color, 4K/30p signal input
	USB(VIEWER /WIRELESS/DC OUT)	USB connector (Type A) x 1 for Memory Viewer function, optional Wireless Module AJ-WM50, power supply (DC 5 V, maximum 2 A)
키스톤 보정	수직 : ±25° / 수평 : ±35°	
렌즈쉬프트	수직: 0~+44 % , 수평: ±20 %	
스피커	모노 10W	
소음	Nomal/Eco : 38 dB / Quiet : 28 dB	
전원	100-240 V AC, 50/60 Hz	
소비전력	[MAX] 420W (4.5-1.9 A) (455VA) , 410W (200-240V) [NORMAL]: 390W (100-120V), 375W (200-240V) [ECO]: 275W (100-120 V), 265W (200-240V) [QUIET]: 270W (100-120V), 260W (200-240V)	
크기(W×H×D)	399 x 133 x 348 mm	
무게	Approximately 7.0kg	